

MAIN PARTICULARS



SHIPS NAME	FAST HERMAN
PREVIOUS NAMES	JOLIE BRISE, FLINTERBRISE
NATIONALITY	Belgium
CALLSIGN	ONIO
PORT OF REGISTRY	Antwerpen
SHIPS TYPE	General dry cargo
REGISTERED OWNERS	Fast Lines Belgium N.V. Ernest van Dijckkaai 15-17, B-2000 Antwerpen
MANAGERS	Fast Baltic Sp. z o.o. ul. Bytomska 7, 70-603 Szczecin
COMMERCIAL MANAGERS	Fast Lines Belgium N.V. Ernest van Dijckkaai 15-17, B-2000 Antwerpen
BUILDERS	Bodewes Shipyards B.V. Hoogezand - Marine Projects Ltd. Gdansk
YARD NUMBER	640
KEEL LAID	29.12.2004
DATE & PLACE OF DELIVERY	09.02.2006, Gdansk, Poland.
IMO NUMBER	9345362
OFFICIAL NUMBER	O 6731
MMSI NUMBER	205689000
INMARSAT - C	420568910
INMARSAT - C	420568911
EMAIL	mv.fastherman@gmail.com
CELLPHONE	+44 7540 123899
AAIC CODE	BE02
CLASSIFICATION	Bureau Veritas I Hull, Mach, Aut-UMS
ICE CLASS	1A Finnish-Swedish Ice Rules 2002
LENGTH OVER ALL	82,50 mtr.
LENGTH PERPENDICULARS	79,54 mtr.
BEAM MAX.	12,60 mtr.
BEAM MOULDED	12,50 mtr.
DEPTH TO MAINDECK	6,80 mtr.
DEPTH TO UPPERDECK	8,00 mtr.
DESIGN DRAUGHT SUMMER	5,30 mtr
SAIMAA DRAUGHT	4,35 mtr.
GROSS TONNAGE	2474
NETT TONNAGE	1464
DEADWEIGHT	3459 t
DISPLACEMENT	4518 t
LIGHT SHIP	1059,4 t
HOLD CAPACITY	188148 cbft.
HOLD DIMENSIONS	59,15 x 10,30/6,00 x 8,98 m (hold narrowing in the fore part)
CLEAR HOLD OPENINGS	33,27 x 10,30 m + 25,47 x 10,30/6,00 m (divided by strong beam)
TANKTOP STRENGTH	13 t/m2
NUMBER OF GRAIN BULKHEADS	2
POSSIBLE POSITIONS OF BULKHEADS	7
CONTAINER CAPACITY	Hold 102 TEU, deck 34 TEU, <u>total 136 TEU</u>
FUEL CAPACITY MDO	277 m3
FUEL CAPACITY GASOIL	34 m3
POTABLE WATER	27 m3
BALLAST WATER	1495 m3
MAIN ENGINE	MAK 6M25 (6 cylinders single acting), <u>1850 kW</u> at 750 rpm.
CPP	Rolls Royce / Kamewa, 4-blade, NiAl-bronze, 2900 mm, 211 rpm.
ROTATION CPP	Counter clockwise, <u>acting right-handed on astern</u> .
BOWTHRUSTER	Veth Jet, <u>220 kW</u> at 1800 rpm. (360 deg) Diameter prop 890 mm.
RUDDER	Balance, angle 2 x 57.5 degrees.
ANCHORS	POOL-TW (2 x) stockless bow anchors 1305 kg each.
ANCHOR CHAIN	PS/SB 8 shackles.
HATCH COVER SYSTEM	Pontoon type steel hatchcovers (10 x), permissible load 1,55 t/m2.

(this is a non-official document. Above information believed to be correct, without any liability to the vessel and her owners)